1U, Single Slide Rail, LCD Keyboard Drawer 8 port PS2 or COMBO KVM Switch







Features

- Meet EIA310c & IEC-3 specification
- 1U, Single Rail, built-in 17 . 3" LCD keyboard drawer 8-port PS2 or Combo KVM switch
- Built-in 17.3" LCD Monitor, 1920x 1080 resolution Option: 17.3", 1600x 900 resolution
- 104-key industrial keyboard with touch pad
- 1U, 520 mm short depth and lightweight
- 2 thumb screws to lock 17.3" LCD monitor
- Built-in rail self-locking device
- Tempered glass protect LCD screen

KVM Switch

- 8 port PS2/ COMBO KVM with military industrial grade production
- Support Password protection and Server name
- Support extra daisy chain port and no waste server port for expansion
- Support Windows, DOS, Netware, Unix, Linux, iMAC, Power MAC and Sun Micro Systems with USB
- Hot Plug- add or remove connected computer without powering off the KVM switch or computer
- No software required. Easy computer selection via Front Push Button, Hot Key, OSD menu
- Firmware upgrades to all the chained KVM switch via the KVM cable connects to port 1 (COMBO KVM only)
- Auto Scan mode. Easy to monitor Server Operation
- Superior Video Bandwidth up to 200MHz
- Keyboard status restored upon Server switched
- LED display for status monitor
- Buzzer sound for Server switched confirmation

Specification

Model No	AMK508-17	AMK508-17W	
Drawer Design	1U, Single Slide Rail self-locking device for 19" rackmount		
Weight	11 kgs		
Dimension	442.4 x 44 x 520 mm (W x H x D)		
Power Supply	Built-in 60W, 90~264VAC, Operating Temp.: -20~70°C		
Construction	Heavy-duty steel		
Keyboard	105-key industrial keyboard with touchpad Option KB: CH, FR, GR, KR, RU, UK, US		
Protection	Tempered glass protect LCD screen		
Physical Security	2 thumb screws to secure LCD monitor		
Power Consumption	3 watts stand-by, 25 watts in-use		
Temperature	Operation: 0 ~ 50°C	Storage: -20 ~ 60°C	
Approvals	CE, FCC class A,RoHS		
LCD Displ	av		

LCD Display

Size	17.3"	17.3"
Resolution	1600 x 900	1920 x 1080

KVM Switch

		PS2 KVM	PS2 & USB COMBO KVM	
Port connection	KVM Port	8-Port		
	Max. Port	Daisy Chain up to 8 levels to support 120 sets		
Port Selection		8x Front Push Buttons, OSD Manu, Hotkey		
Switch	Port Selection	8x Front Push Buttons		
	Reset	1x push button		
	Power	1x Rocker Switch		
	LCD on/off	1x Front standby Push button		
	LCD control	4x LCD adjust push buttons		
LED	Operation	8		
	Power	8		
	Keyboard Lock	Num Lock, Caps Lock, Scroll Lock		
KVM Cable		8x 1.8m PS2 cable	8x 1.8m USB cable	

Ordering Information

AMK508-17PBUS

1U, 17.3", 1600x 900, 8 ports PS2 KVM switch with 8 x 1.8m PS2 cable

AMK508-17CBUS

1U, 17.3", 1600x 900, 8 ports Combo KVM switch with 8 x 1.8m USB cable AMK508-17WPBUS

1U, 17,3", 1920x 1080, 8 ports PS2 KVM switch with 8 x 1.8m PS2 cable

AMK508-17WCBUS

1U, 17.3" 1920x 1080, 8 ports Combo KVM switch with 8 x 1.8m USB cable

Option

- 80W, 24~48 VDC Power Supply
- 1.8m, 3.0 m, 5.0 m KVM cable
- Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US