

# TO-1608BC-MRE


## Surface Mount Device LED

Part Number	Chip		Lens Color
	Material	Source Color	
TO-1608BC-MRE	AlGaInP	Ultra Bright Red	Water Clear

### Features

- IC compatible
- Compatible with automatic placement equipment
- Compatible with infrared and vapor phase reflow soldering process
- Top view type
- Pack in 8 mm tape on 7" diameter reel
- RoHS compliant
- Moisture sensitivity Level: level 3

### Dimensions



**Notes:**

1. All dimensions are in millimeter.
2. Tolerance is  $\pm 0.1$ mm unless individual mark noted.

### Absolute Maximum Rating @ Ta=25°C

Parameter	Maximum Rating	Unit
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	80	mA
Power Dissipation	75	mW
Continuous Forward Current	25	mA
Reverse Voltage	5	V
Operating Temperature Range	-55°C to +85°C	
Storage Temperature Range	-55°C to +105°C	
IR Reflow Soldering Profile For Lead Free Soldering	260°C	

### Electrical / Optical Characteristic @ Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I <sub>v</sub>	51		146	mcd	I <sub>F</sub> =20mA
Viewing Angle	2θ <sub>1/2</sub>		120		deg	I <sub>F</sub> =20mA
Forward Voltage	V <sub>F</sub>		2.0		V	I <sub>F</sub> =20mA
Dominant Wavelength	λ <sub>d</sub>		630		nm	I <sub>F</sub> =20mA
Spectral Line Half-Width	Δλ		15		nm	I <sub>F</sub> =20mA
Reverse Current	I <sub>R</sub>			10	μA	V <sub>R</sub> =5V

## Bin Code List for Reference

Luminous Intensity		Unit : mcd@20mA
Bin Code	Min	Max
E1	51	66
E2	66	86
E3	86	112
E4	112	146

Tolerance of Luminous Intensity on each bin is  $\pm 15\%$

Dominant Wavelength		Unit : nm@20mA
Bin Code	Min	Max
624627	624	627
627630	627	630
630633	630	633
633636	633	636

Tolerance of Dominant Wavelength on each bin is  $\pm 1\text{nm}$