


Data sheet Product BLR 3 025 Z




PCB connectors>Female headers
for \varnothing 0.35...0.43 mm

Features

grid:	1.27 mm
no. of contacts:	25
contact material:	CuZn-alloy
contact sleeve:	tin-plated
surface contact / contact sleeve:	Ni+4...6µm Sn
contact spring:	gold-plated
inner contact spring material:	CuBe-alloy
inner contact spring surface:	Ni+0,25µm Au
type internal spring:	3-fingers
plugability for circuit points:	Ø0,35...0,46mm
insert depth:	2.5...3mm
insertion / drawing force:	1.2N/0.6N
shock resistance:	50 g
volume resistance:	≤20 mΩ
vibration resistance max.:	15 g
capacity between two adjacent contacts:	≤1,0 pF
nominal current:	1 A
nominal voltage:	100 V DC
test voltage:	500 V
insulating body material:	PCT, GF
temperature range:	<ul style="list-style-type: none">• -40°C... +105°C• (260°C/10 s)
class of inflammability:	UL 94 V-0
version:	standard
connection type:	THT (soldering)
reflow solderable:	yes

Technical Drawing



Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de