


DT-2000-TB

114-Key NEMA 4X Keyboard with Integrated 38mm Trackball Pointing Device



IKEY Industrial Peripherals
2621 Ridgepoint Dr., Suite 235
Austin, TX 78754
800.866.6506 Telephone
512.837.0207 Fax

INDUSTRIAL RATINGS

NEMA 4, 4X, 12
UL-1950
CE
FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

TRACKBALL

BALL: 38mm Epoxy Resin
CASE: Stainless steel
Switches: Stainless Steel

POWER

KEYBOARD: 5V@10ma (from CPU port)
TRACKBALL: 10ma (from mouse conn. port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK: 3x11 ms pulses of 50g on each of 3 axes

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

FEATURES

NEMA 4X Rated
24 Function Keys
Sealed Optical Trackball
Stainless Steel Case
3 Stainless Steel Switches
Industrial Silicone Rubber Pad

DIMENSIONS: (W-H-D) 20.25" x 7.75" x 2.125"
514.35mm x 196.857 x 53.97mm

CABLE LENGTH: 10 feet (3.94 meters)

COMPATIBILITY

KEYBOARD: PS/2, USB, AT
TRACKBALL: PS/2, USB

WARRANTY: 1 Year Limited Warranty

