


LEAD FINISH:	SOLDER
EYELET FINISH:	SOLDER
CAPACITANCE	3000PF MIN.
TEMP. RANGE	-55°C TO 125°C
CURRENT	15 AMP MAX.
WORKING VOLTAGE	85°C 125 VDC MAX. 125°C 200 VDC MAX.
D.C. RESISTANCE	.01ohms MAX.
MIN. I.L. PER MIL-STD-220 AT 25°C NO LOAD	
FREQ. MHZ	I.L. (db)
10	7
50	--
100	50
200	--
1 GHZ	65
10 GHZ	65

SCHEMATIC

MARKING:

PART: NONE  
 BAG: 1223-012  
 DATE CODE  
 QTY./BAG (200 MAX.)

07	CN. 206583	REV. <input type="checkbox"/>	TOLERANCES UNLESS OTHERWISE SPECIFIED
06	CN. 202458	CHANGE NOTICE	Fractions $\pm 1/64$
05	CN. 201267		Dec. .xxx $\pm$
04	CN. 184995 REDRAWN		Dec. .xxx $\pm .010$
			Angles $\pm 0^\circ 30'$
			CODE IDENT. ND, DLS P2

  
 SPECTRUM CONTROL, INC.  
 ERIE, FAIRVIEW  
 PENNSYLVANIA

Dwn. KAUFFMAN  
 Ckd. 4/9/02  
 Apvd  
 Scale NONE

Description  
 P1 SOLDER-IN FILTER  
 1223-012