

SL-81

81 Key Illuminated Industrial Keyboard



IKEY Industrial Peripherals
2621 Ridgepoint Dr., Suite 235
Austin, TX 78754
800.866.6506 Telephone
512.837.0207 Fax

INDUSTRIAL RATINGS

NEMA 4, 4X 12
UL-1950
CE
FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.060" (1.5mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER

KEYBOARD: 5V@10ma (from CPU port)
BACKLIGHT: 5V@200ma (from CPU port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 80%

SHOCK: 3x11 ms pulses of 50g on each of 3 axes

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

FEATURES

12 Function Keys

DIMENSIONS: (W-H-D) 13" x 7" x 1.9"
330.2mm x 177.8mm x 48.3mm

CABLE LENGTH: 10 feet (3.048 meters)

BACKLIGHTING

Four levels of backlighting (including off)
Low ma green LEDs (red also available)
Operates from button on keyboard

COMPATIBILITY: PS/2, AT, Windows, and NT

WARRANTY: 1 Year Limited Warranty

