# **Dual D Flip-Flop with Set and Reset**

# **High-Performance Silicon-Gate CMOS**

The MC74HC74A is identical in pinout to the LS74. The device inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LSTTL outputs.

This device consists of two D flip-flops with individual Set, Reset, and Clock inputs. Information at a D-input is transferred to the corresponding Q output on the next positive going edge of the clock input. Both Q and  $\overline{Q}$  outputs are available from each flip-flop. The Set and Reset inputs are asynchronous.

#### **Features**

- Pb-Free Packages are Available\*\*
- Output Drive Capability: 10 LSTTL Loads
- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2.0 to 6.0 V
- Low Input Current: 1.0 μA
- High Noise Immunity Characteristic of CMOS Devices
- In Compliance with the JEDEC Standard No. 7.0 A Requirements
- Chip Complexity: 128 FETs or 32 Equivalent Gates




Figure 1. LOGIC DIAGRAM

# **FUNCTION TABLE**

	Inp	Out	puts		
Set	Reset	Clock	Data	ø	Q
L	Н	Χ	Χ	Н	L
Н	L	Χ	Χ	L	Н
L	L	Χ	X	H*	H*
Н	Н		Н	Н	L
Н	Н	$\mathcal{L}$	L	L	Н
Н	Н	L	X	No C	hange
Н	Н	Н	X	No C	hange
Н	Н	~	Χ	No Cl	hange

<sup>\*</sup>Both outputs will remain high as long as Set and Reset are low, but the output states are unpredictable if Set and Reset go high simultaneously.




# ON Semiconductor®

http://onsemi.com

# MARKING DIAGRAMS




PDIP-14 N SUFFIX CASE 646





SOIC-14 D SUFFIX CASE 751A






TSSOP-14 DT SUFFIX CASE 948G



A = Assembly Location
WL or L = Wafer Lot
YY or Y = Year

WW or W = Work Week

#### **PIN ASSIGNMENT**



# ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

<sup>\*\*</sup>For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

#### **MAXIMUM RATINGS**

Symbol	Parameter	Value	Unit
V <sub>CC</sub>	DC Supply Voltage (Referenced to GND)	- 0.5 to + 7.0	V
V <sub>in</sub>	DC Input Voltage (Referenced to GND)	$-0.5$ to $V_{CC} + 0.5$	V
V <sub>out</sub>	DC Output Voltage (Referenced to GND)	$-0.5$ to $V_{CC} + 0.5$	V
I <sub>in</sub>	DC Input Current, per Pin	± 20	mA
I <sub>out</sub>	DC Output Current, per Pin	± 25	mA
I <sub>CC</sub>	DC Supply Current, V <sub>CC</sub> and GND Pins	± 50	mA
P <sub>D</sub>	Power Dissipation in Still Air, Plastic DIP† SOIC Package† TSSOP Package†	750 500 450	mW
T <sub>stg</sub>	Storage Temperature	- 65 to + 150	°C
TL	Lead Temperature, 1 mm from Case for 10 Seconds (Plastic DIP, SOIC or TSSOP Package)	260 300	°C

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high–impedance circuit. For proper operation,  $V_{in}$  and  $V_{out}$  should be constrained to the range GND  $\leq$  ( $V_{in}$  or  $V_{out}$ )  $\leq$   $V_{CC}$ .

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

†Derating — Plastic DIP: – 10 mW/°C from 65° to 125°C

SOIC Package: - 7 mW/°C from 65° to 125°C

TSSOP Package: - 6.1 mW/°C from 65° to 125°C

For high frequency or heavy load considerations, see Chapter 2 of the ON Semiconductor High-Speed CMOS Data Book (DL129/D).

#### RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter			Max	Unit
V <sub>CC</sub>	DC Supply Voltage (Referenced to GND)		2.0	6.0	V
V <sub>in</sub> , V <sub>out</sub>	DC Input Voltage, Output Voltage (Referenced to GND)		0	$V_{CC}$	V
T <sub>A</sub>	Operating Temperature, All Package Types		- 55	+ 125	°C
t <sub>r</sub> , t <sub>f</sub>	(Figures 1, 2, 3) V	CC = 2.0 V CC = 3.0 V CC = 4.5 V CC = 6.0 V	0 0 0	1000 600 500 400	ns

## ORDERING INFORMATION

Device	Package	Shipping <sup>†</sup>
MC74HC74AN	PDIP-14	2000 Units / Box
MC74HC74ANG	PDIP-14 (Pb-Free)	2000 Units / Box
MC74HC74AD	SOIC-14	55 Units / Rail
MC74HC74ADR2	SOIC-14	2500 Units / Reel
MC74HC74ADR2G	SOIC-14 (Pb-Free)	2500 Units / Reel
MC74HC74ADT	TSSOP-14*	96 Units / Rail
MC74HC74ADTR2	TSSOP-14*	2500 Units / Reel

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

<sup>\*</sup>This package is inherently Pb–Free.

# DC ELECTRICAL CHARACTERISTICS (Voltages Referenced to GND)

				Gu	aranteed Li	mit	
Symbol	Parameter	Test Conditions	V <sub>CC</sub> V	– 55 to 25°C	≤ <b>85</b> °C	≤ 125°C	Unit
V <sub>IH</sub>	Minimum High-Level Input	$V_{out} = 0.1 \text{ V or } V_{CC} - 0.1 \text{ V}$	2.0	1.5	1.5	1.5	V
	Voltage	$ I_{Out}  \leq 20 \mu\text{A}$	3.0	2.1	2.1	2.1	
			4.5	3.15	3.15	3.15	
			6.0	4.2	4.2	4.2	
V <sub>IL</sub>	Maximum Low-Level Input	$V_{out} = 0.1 \text{ V or } V_{CC} - 0.1 \text{ V}$	2.0	0.5	0.5	0.5	V
	Voltage	$ I_{out}  \le 20 \mu A$	3.0	0.9	0.9	0.9	
			4.5	1.35	1.35	1.35	
			6.0	1.8	1.8	1.8	
V <sub>OH</sub>	Minimum High-Level Output	$V_{in} = V_{IH}$ or $V_{IL}$	2.0	1.9	1.9	1.9	V
	Voltage	$ I_{out}  \leq 20 \mu A$	4.5	4.4	4.4	4.4	
			6.0	5.9	5.9	5.9	
		$V_{in} = V_{IH} \text{ or } V_{IL}   I_{out}  \leq 2.4 \text{ mA}$	3.0	2.48	2.34	2.2	
		$ I_{out}  \le 4.0 \text{ mA}$	4.5	3.98	3.84	3.7	
		$ I_{out}  \le 5.2 \text{ mA}$	6.0	5.48	5.34	5.2	
V <sub>OL</sub>	Maximum Low-Level Output	$V_{in} = V_{IH}$ or $V_{IL}$	2.0	0.1	0.1	0.1	V
	Voltage	$ I_{out}  \leq 20 \mu A$	4.5	0.1	0.1	0.1	
			6.0	0.1	0.1	0.1	
		$V_{in} = V_{IH} \text{ or } V_{IL}   I_{out}  \leq 2.4 \text{ mA}$	3.0	0.26	0.33	0.4	
		$ I_{out}  \le 4.0 \text{ mA}$	4.5	0.26	0.33	0.4	
		$ I_{out}  \le 5.2 \text{ mA}$	6.0	0.26	0.33	0.4	
I <sub>in</sub>	Maximum Input Leakage Current	V <sub>in</sub> = V <sub>CC</sub> or GND	6.0	± 0.1	± 1.0	± 1.0	μΑ
I <sub>CC</sub>	Maximum Quiescent Supply Current (per Package)	$V_{in} = V_{CC}$ or GND $I_{out} = 0 \mu A$	6.0	2.0	20	80	μΑ

NOTE: Information on typical parametric values can be found in Chapter 2 of the ON Semiconductor High-Speed CMOS Data Book (DL129/D).

# AC ELECTRICAL CHARACTERISTICS ( $C_L = 50 \text{ pF}$ , Input $t_f = t_f = 6.0 \text{ ns}$ )

			Gu	aranteed Li	mit	_
Symbol	Parameter	V <sub>CC</sub> V	– 55 to 25°C	≤ <b>85</b> °C	≤ 125°C	Unit
f <sub>max</sub>	Maximum Clock Frequency (50% Duty Cycle) (Figures 1 and 4)	2.0 3.0 4.5 6.0	6.0 15 30 35	4.8 10 24 28	4.0 8.0 20 24	MHz
t <sub>PLH</sub> , t <sub>PHL</sub>	Maximum Propagation Delay, Clock to Q or Q (Figures 1 and 4)	2.0 3.0 4.5 6.0	100 75 20 17	125 90 25 21	150 120 30 26	ns
t <sub>PLH</sub> , t <sub>PHL</sub>	Maximum Propagation Delay, Set or Reset to Q or $\overline{\mathbb{Q}}$ (Figures 2 and 4)	2.0 3.0 4.5 6.0	105 80 21 18	130 95 26 22	160 130 32 27	ns
t <sub>TLH</sub> , t <sub>THL</sub>	Maximum Output Transition Time, Any Output (Figures 1 and 4)	2.0 3.0 4.5 6.0	75 30 15 13	95 40 19 16	110 55 22 19	ns
C <sub>in</sub>	Maximum Input Capacitance	_	10	10	10	pF

NOTE: For propagation delays with loads other than 50 pF, and information on typical parametric values, see Chapter 2 of the ON Semiconductor High-Speed CMOS Data Book (DL129/D).


		Typical @ 25°C, V <sub>CC</sub> = 5.0 V	
$C_PD$	Power Dissipation Capacitance (Per Flip–Flop)*	32	pF

<sup>\*</sup> Used to determine the no–load dynamic power consumption: P<sub>D</sub> = C<sub>PD</sub> V<sub>CC</sub><sup>2</sup>f + I<sub>CC</sub> V<sub>CC</sub>. For load considerations, see Chapter 2 of the ON Semiconductor High–Speed CMOS Data Book (DL129/D).

# **TIMING REQUIREMENTS** (Input $t_f = t_f = 6.0 \text{ ns}$ )

			Gu	aranteed Li	mit	
Symbol	Parameter	v <sub>cc</sub> v	– 55 to 25°C	≤ <b>85</b> °C	≤ 125°C	Unit
t <sub>su</sub>	Minimum Setup Time, Data to Clock (Figure 3)	2.0 3.0 4.5 6.0	80 35 16 14	100 45 20 17	120 55 24 20	ns
t <sub>h</sub>	Minimum Hold Time, Clock to Data (Figure 3)	2.0 3.0 4.5 6.0	3.0 3.0 3.0 3.0	3.0 3.0 3.0 3.0	3.0 3.0 3.0 3.0	ns
t <sub>rec</sub>	Minimum Recovery Time, Set or Reset Inactive to Clock (Figure 2)	2.0 3.0 4.5 6.0	8.0 8.0 8.0 8.0	8.0 8.0 8.0 8.0	8.0 8.0 8.0 8.0	ns
t <sub>w</sub>	Minimum Pulse Width, Clock (Figure 1)	2.0 3.0 4.5 6.0	60 25 12 10	75 30 15 13	90 40 18 15	ns
t <sub>w</sub>	Minimum Pulse Width, Set or Reset (Figure 2)	2.0 3.0 4.5 6.0	60 25 12 10	75 30 15 13	90 40 18 15	ns
t <sub>r</sub> , t <sub>f</sub>	Maximum Input Rise and Fall Times (Figures 1, 2, 3)	2.0 3.0 4.5 6.0	1000 800 500 400	1000 800 500 400	1000 800 500 400	ns

# **SWITCHING WAVEFORMS**







Figure 2.

Figure 3.






Figure 4.

Figure 5.





Figure 6. EXPANDED LOGIC DIAGRAM

# **PACKAGE DIMENSIONS**

# PDIP-14 **N SUFFIX** CASE 646-06 ISSUE N






- NOTES:
  1. DIMENSIONING AND TOLERANCING
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
   CONTROLLING DIMENSION: INCH.
   DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
   DIMENSION B DOES NOT INCLUDE MOLD FLASH.
   ROUNDED CORNERS OPTIONAL.

	INCHES MILLIM			IETERS
DIM	MIN	MAX	MIN	MAX
Α	0.715	0.770	18.16	18.80
В	0.240	0.260	6.10	6.60
C	0.145	0.185	3.69	4.69
D	0.015	0.021	0.38	0.53
F	0.040	0.070	1.02	1.78
G	0.100	BSC	2.54	BSC
Н	0.052	0.095	1.32	2.41
J	0.008	0.015	0.20	0.38
K	0.115	0.135	2.92	3.43
L	0.290	0.310	7.37	7.87
M		10 °		10 °
N	0.015	0.039	0.38	1.01

# SOIC-14 **D SUFFIX** CASE 751A-03 ISSUE G



#### NOTES:

- AND LES:

  1. DIMENSIONING AND TOLERANCING PER
  ANSI Y14.5M, 1982.


  2. CONTROLLING DIMENSION: MILLIMETER.
  3. DIMENSIONS A AND B DO NOT INCLUDE
  MOLD PROTRUSION.

  4. MAXIMUM MOLD PROTRUSION 0.15 (0.006)
- 4. MAXIMUM MOLD PROTRUSION 0.15 (0.00 PER SIDE.
  5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INC	HES	
DIM	MIN	MAX	MIN	MAX	
Α	8.55	8.75	0.337	0.344	
В	3.80	4.00	0.150	0.157	
С	1.35	1.75	0.054	0.068	
D	0.35	0.49	0.014	0.019	
F	0.40	1.25	0.016	0.049	
G	1.27	BSC	0.050	BSC	
J	0.19	0.25	0.008	0.009	
K	0.10	0.25	0.004	0.009	
M	0 °	7°	0°	7°	
Р	5.80	6.20	0.228	0.244	
R	0.25	0.50	0.010	0.019	

# **PACKAGE DIMENSIONS**

# TSSOP-14 **DT SUFFIX** CASE 948G-01 **ISSUE O**



- NOTES:
  1. DIMENSIONING AND TOLERANCING PER ANSI
- DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
  CONTROLLING DIMENSION: MILLIMETER.
  DIMENSION A DOES NOT INCLUDE MOLD FLASH, PROTFUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
  DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION. AND EXCEED 0.25 (0.010) PER SIDE.
- PROTRUSION SHALL NOT EXCEED
  0.25 (0.010) PER SIDE.
  DIMENSION K DOES NOT INCLUDE DAMBAR
  PROTRUSION. ALLOWABLE DAMBAR
  PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN
  EXCESS OF THE K DIMENSION AT MAXIMUM
  MATERIAL CONDITION.
  TERMINAL NUMBERS ARE SHOWN FOR
  REFERENCE ONLY.
  DIMENSION A AND B ARE TO BE DETERMINED
  AT DATUM PLANE -W-.

	MILLIN	IETERS	TERS INCHES		
DIM	MIN	MAX	MIN	MAX	
Α	4.90	5.10	0.193	0.200	
В	4.30	4.50	0.169	0.177	
C		1.20		0.047	
D	0.05	0.15	0.002	0.006	
F	0.50	0.75	0.020	0.030	
G	0.65	BSC	0.026	BSC	
Н	0.50	0.60	0.020	0.024	
ſ	0.09	0.20	0.004	0.008	
J1	0.09	0.16	0.004	0.006	
K	0.19	0.30	0.007	0.012	
K1	0.19	0.25	0.007	0.010	
L	6.40		0.252 BSC		
М	0°	8°	0°	8°	

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

# **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 61312, Phoenix, Arizona 85082–1312 USA Phone: 480–829–7710 or 800–344–3860 Toll Free USA/Canada Fax: 480–829–7709 or 800–344–3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center 2–9–1 Kamimeguro, Meguro–ku, Tokyo, Japan 153–0051 Phone: 81–3–5773–3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.