## COMPONENT SPECIFICATION

Name Ferrite Chip EMI Suppressors COMPOSITE SPECIFICATION 1/2

#### 1. SCOPE

This specification applies to the MLB-2012 series Ferrite Chip EMI suppressors.

#### 2. STANDARD ATMOSPHERIC CONDITIONS

Unless otherwise specified the standard range of atmospheric conditions for making measurements and tests is as follows:

Ambient temperature :  $20\pm15^{\circ}$ C Relative humidity :  $30\sim70\%$ 

If there may be any doubt on the results, measurements shall be made within

the following limits:


Ambient temperature : 25±5 °C Relative humidity : 30~70%

3. RATINGS

		*		
IMPEDANCE (Ω)	DC RESISTANCE	RATED CURRENT		
AT100 MHz 500mV	(Ω) Max	(mA) Max		
600±25%	0.09	2000		

%The maximum rated current : the DC current value having temperature increased 40  $\,^{\circ}$ C after thru DC current 2 hours at ambient temperature.

### 4. DIMENSION



OPERATING TEMP. RANGE :  $-55^{\circ}$ C ~  $+125^{\circ}$ C STORAGE TEMP. RANGE :  $-10^{\circ}$ C ~  $+40^{\circ}$ C

Ш	W	T	Α			
2±0.2	1.25±0.2	0.9-0.2/+0.15	0.2~0.8			
(0.079±0.008)	(0.049±0.008)	(0.035-0.008/+0.006)	(0.008~0.031)			

# 5. The place of origin:

### **Taiwan**

HISTORY	DATE	REVISION		SIGN.	SIGN.
PLANNED BY	CHECKED BY	APPROVED BY			
		1			

## **COMPONENT SPECIFICATION**

