

SHIELDED TYPE

CDRH5D28





Outline

SMT type power inductors whereby the electrode is attached to the ferrite core directly. They are also magnetically shielded to prevent noise radiation.

Dimensions (mm)

LAND PATTERNS(mm)

CONSTRUCTION


(2.5 μ H – 100 μ H)

◆ TYPE CDRH5D28

Parts No.	Inductance	D.C.R. (Ω) (Max) Typical / Rated D. C. Current (A)	Parts No.	Inductance	D.C.R. (Ω) (Max) Typical / Rated D. C. Current (A)
1R0	1.0 μ H		7R4	7.4 μ H	
1R2	1.2 μ H		8R2	8.2 μ H	53m (39m) / 1.60
1R5	1.5 μ H		8R6	8.6 μ H	
1R8	1.8 μ H		8R7	8.7 μ H	
2R2	2.2 μ H		8R9	8.9 μ H	
2R5	2.5 μ H	18m (13m) / 2.60	100	10 μ H	65m (48m) / 1.30
2R7	2.7 μ H		120	12 μ H	76m (56m) / 1.20
3R0	3.0 μ H	24m (18m) / 2.40	150	15 μ H	0.103 (76m) / 1.10
3R3	3.3 μ H		180	18 μ H	0.110 (82m) / 1.00
3R9	3.9 μ H		220	22 μ H	0.122 (90m) / 0.90
4R1	4.1 μ H		270	27 μ H	0.175 (0.130) / 0.85
4R2	4.2 μ H	31m (23m) / 2.20	330	33 μ H	0.189 (0.140) / 0.75
4R7	4.7 μ H		390	39 μ H	0.212 (0.157) / 0.70
5R0	5.0 μ H		470	47 μ H	0.260 (0.185) / 0.62
5R3	5.3 μ H	38m (28m) / 1.90	560	56 μ H	0.305 (0.226) / 0.58
5R4	5.4 μ H		680	68 μ H	0.355 (0.263) / 0.52
5R6	5.6 μ H		820	82 μ H	0.463 (0.343) / 0.46
6R0	6.0 μ H		101	100 μ H	0.520 (0.385) / 0.42
6R2	6.2 μ H	45m (33m) / 1.80	121	120 μ H	
6R8	6.8 μ H		151	150 μ H	
7R3	7.3 μ H		181	180 μ H	

Measuring Freq. (L)

CDRH5D28 10kHz

Tolerance of Inductance

CDRH5D28 $\pm$ 30% (N)

Rated D.C. Current

This indicates the value of current when the inductance is 75%(65%) more than its nominal value and temperature rising $t=40^{\circ}\text{C}$ lower at D.C. superimposition.

Sales Contact

North America

1701 Golf Road, Tower 3
Suite 400, Rolling
Meadows, IL 60008, USA
Tel: (1) 847 545-6700
Fax: (1) 847 545-6720

Japan

Nihonbashi- ingyocho
2-Chome, Chuo-ku,
Tokyo, Japan
Tel: (81) 03 3667-3301
Fax: (81) 03 3667-3456

Hong Kong

14/F, Eastern Centre,
1065 King's Road, Quarry
Road, Hong Kong
Tel: (852) 2880-6688
Fax: (852) 2880-9596

Taiwan

No. 171, Futech Street,
Hsin-I, Taipei, Taiwan,
ROC
Tel: (886) 2 2726-2177
Fax: (886) 2 2728-2726

Singapore

996 Bendemeer
Road #04-05 to 06
Singapore 339944
Tel: (65) 2963-388
Fax: (65) 2963-390

Europe

Chaussee de Tervuren113A,
1160 Brussels
Belgium
Email:
europe.sales@hk.sumida.com