



▶ Computer Pointing Devices

DT-OM

Technical Specifications

Features and Benefits:

- ▶ **AquaPoint™**
- ▶ Meets NEMA 4X Specifications
- ▶ Optical Tracking Technology
- ▶ Solid State Construction
- ▶ Industrial Silicone Overlay
- ▶ ABS Polycarbonate Frame
- ▶ Smooth Button Surface
- ▶ Comfortable, Ergonomic Design
- ▶ Available with USB or PS/2 Cables

INDUSTRIAL APPROVALS

NEMA 4X
FCC Class 15, Part B, CE Rating, UL-1950

KEY SWITCH

MATERIAL: Industrial silicone rubber
FEEDBACK: Tactile with mechanical snap

POWER

5V@50ma (from mouse conn. port)

TEMPERATURE RANGE

-40C to +90C

HUMIDITY: 100% Resistant

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

WEIGHT

0.4 lb (0.18 kg)

DIMENSIONS

(W-H-D) 2.58" x 1.56" x 5"
65.5mm x 39.7mm x 127mm

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

CABLE

LENGTH: 6 Feet
DESIGN: PS/2 or USB cable

COMPATIBILITY

USB: All Windows and Macintosh OS
PS/2: All Windows Operating Systems

WARRANTY: 1 Year Limited Warranty

MODEL NUMBERS:

DT-OM-PS2: With PS/2 cable
DT-OM-USB: With USB cable



© 2005 IKEY, Ltd.

HOLLIS
TECHNOLOGIES

Represented By:

Hollis Technologies, Inc. Serving New England and Eastern NY

Phone: 603-577-8958 • Info: sales@hollis-tech.com | www.hollis-tech.com