

Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of BNX002-01 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-sg/products/productdetail?partno=BNX002-01

BNX002-01

In Production RoHS REAC

Appearance & Shape







Other Usage	For general
-------------	-------------

Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	Box	100



The block type "EMIFIL" BNX series incorporates through-type capacitor, monolithic chip capacitors and bead. The BNX is high performance for use in DC power circuits.

Features

- 1. The filter enables obtaining high insertion loss in wide frequency ranges from 0.5MHz to 1GHz.
- 2. Effective for impulse noise such as electrostatic discharge or spike noise.
- 3. There are no connection routes in the current circuits, thus ensuring highly reliable performance.

Applications

- 1. Displays (PDP/LCD-TV)
- 2. Digital AV equipment
- 3. Amusement equipment
- 4. PC peripheral equipment
- 5. Industry equipment

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



1 of 3



BNX002-01

Note: This datasheet may be out of date.

Please download the latest datasheet of BNX002-01 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-sg/products/productdetail?partno=BNX002-01



Shape Lead Length 12.0mm Length Tolerance ±0.5mm Width 11.0mm Width Tolerance ±0.5mm Thickness 13.0mm Thickness Tolerance max. Rated Current 10A Operating Temperature Range -30°C to 85°C Mass(typ.) 3.0g Rated Voltage 50Vdc 125Vdc Withstanding Voltage Insulation Resistance(max.) 100MΩ 1MHz to 1GHz:40dB min. (Line Insertion Loss impedance= 50Ω)

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.


Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering


Product Search Data Sheet



BNX002-01

Product Data





Insertion Loss Characteristics

Equivalent Circuit

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date.

Please download the latest datasheet of BNX002-01 from the official website of Murata Manufacturing Co., Ltd. http://www.murata.com/en-sg/products/productdetail?partno=BNX002-01

3 of 3