



Pitch range in mm		Nominal dimension range in mm	
over	over	over	over
6	10	6	30
to	to	to	to
10	24	30	90
to	to	to	to
10	24	50	200
to	to	to	to
10	24	90	480
to	to	to	to
10	15	±0.25	±0.1
to	to	±0.2	±0.3
to	to	±0.5	±0.7
to	to	±0.5	±0.7

- Notes:
1. Pitch: 5.08mm, Poles: 2-24P
  2. Rated voltage: 300V
  3. Rated current: 15A
  4. Withstanding voltage: AC2000V/1Min.
  5. Insulation resistance: 5000M $\Omega$ /DC1000V
  6. Temp. Range: -40° C~+105° C
  7. Undimensioned Tolerances:

REVISION RECORD			
REV	ECO	DESCRIPTION	DATE
△		Drawing amend	04/20/06
△		增加环保标示	Ye j 10/30/07

2	2EDGR Pin header	1008B00040 (H)	XX	Brass	SnCe
1	HT508V Housing	1027A0YXXA (H)	1	PA66	UL94V-0

  

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES

  

DETACHED LISTS	
MM (INCH)	MM (INCH)
0 ± .005	± .005
± .005	± .005
ANGLES ± 1°	
THIRD ANGLE PROJECTION	

  

DATE	DATE	DATE	DATE
08/03/04			

  

NAME	DRAWING NO.	SIZE
HT508R-5.08-XXP-1Y-00A(H)	HT508R-E01	A3

  

SCALE	DO NOT SCALE DRAWING	SHEET	OF
1:1		1	1

