



SPECIFICATION

CONTACT RESISTANCE: 30mΩ MAX.
 INSULATION RESISTANCE: 100MΩ MIN/500V DC
 DIELECTRIC STRENGTH: 500V AC FOR 1MINUTE
 LIFE CYCLE: 5,000 CYCLES MIN.
 OPERATION TEMPERATURE RANGE: -25°C-80°C
 INSERTION & EXTRACTION FORCE: 4N-20N
 (0.4kgf-2kgf)

LET	PART NAME	MATERIAL	QTY	FINISH	TOLERANCE	SCALE	DATE	DESIG	DRAW	INSPE	APRO
6	ナット NUT	BSBM	1	NI	±0.3	4/1	/ /				
5	スリット端子 TERMINAL	BSR t=0.3	1	NI	MODEL		QTY	PART NAME	2.5φ3極シヤック		
4	リングハズ CONTACT 2	FAB-EH t=0.25	1	AU	型式			品名			
3	チップハズ CONTACT 1	FAB-EH t=0.25	1	NI	MATERIAL				DRAW. NO	RM-603M	
2	ケース BODY	PBT-G30%	1		材質				図番		
1	メタル METAL	BSBM	1	NI	FINISH						
					地理		大 恵 電 子 部 品				