



NOTES:
 MATERIAL:
 BODY: NYLON66 WITH GLASS FIBER, BLACK
 CONTACT: PHOSPHOR BRONZE.
 FINISH:
 CONTACT: SN ONLY (MATTE) 100u" PLATED OVER
 NI 30u" UNDER-PLATING.
 SPECIFICATION:
 APPLICATION: FOR 3V LITHIUM BATTERY (CR2032)
 CONTACT RESISTANCE: 30 mΩ MAX.
 INSULATOR RESISTANCE: 5000 MΩ MIN.
 OPERATION TEMPERATURE: -55°C TO +105°C.
 DURABILITY: 50 CYCLES.

PCB LAYOUT

RoHS Compliant		HSM 玄茂科技股份有限公司		HSUAN MAO TECHNOLOGY CO., LTD.	
APPD. 核准 Betty	SCALE 比例 參考	TOLERANCE 容許公差 X ±0.38 X ±2' XX ±0.25 X ±1' .XXX ±0.15	PART NAME 品名 BATTERY HOLDERS BH7 TYPE BLACK INSULATOR ROHS LOW-LEAD		
DWG. 製圖 Jolin			UNIT 單位 MM	SIZE. 紙張尺寸 A 4	PART NO. 料號 C0170-02STB000R
DATE 制表日 2007/03/29	PAGE 張數 1 / 1	REV. 版次 A			