



M39012/56-3107

REVISIONS	
ISSUE	CHANGES
0	ER 34288 KH 11/20/92
1	CN 35318 C KH 02/08/94

DET1131

- NOTES:**
- FOR USE WITH M17/119-RG174, /173-00001, /113-RG316 & M17/172-00001 CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-559.
 - INTERFACE PER MIL-STD-348, FIG. 310-1.
 - MARK PACKAGE: KINGS 876-60-3
 - MATERIALS:
 INSULATORS: TEFLON, ASTM-D-1457
 GASKETS: & O-RINGS: SIL. RUBBER, ZZ-R-765
 C-RING & MALE/FEMALE CENTER CONTACT: BER. COP., ASTM-B-196
 MALE CENTER CONTACT: BRASS, ASTM-B16
 ALL OTHER METAL PARTS: ST. STEEL, 303
 - FINISHES:
 CENTER CONTACTS: HARD GOLD PLATE PER MIL-G-45204
 ALL OTHER METAL PARTS: PASSIVATED PER QQ-P-35
 - ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 50 OHMS
 VOLTAGE RATING: 250 VOLTS RMS
 FREQUENCY RANGE: DC TO 12.4GHz

STAMP: 91836 M39012/56-3107 XX XX
 DATE CODE

SCALE 8:1	
APPROX SURFACE AREA 876-60-3	
USED ON	
REF:	
PLUG, SMA, ANGLE, W/P TAPER GRIP	
DRAWN MJB	DATE 10/01/92
DESIGN GA	DATE 04/27/93
APPR.	DATE
KINGS ELECTRONICS CO., INC. TUCKAHOE, NEW YORK 10707	
M39012/56-3107	