



REVISIONS			
REV	DESCRIPTION	DATE	CHANGED BY
A	PER ECN 51979, PROD REL	13DEC04	HL
B	PER ECN 52088	15FEB05	HL
C	PER ECN 52237,ROHS COMPL	25MAY05	EB
D	PER ECN 52725	31MAY06	HL

HEAD WIRING

CONN	SIGNAL	COLOR
1	HEAD CASE (GND)	BLACK
2	READ HEAD TK1	WHITE
3	READ HEAD TK1	YELLOW
4	READ HEAD TK2	RED
5	READ HEAD TK2	GREEN

NOTES: UNLESS OTHERWISE SPECIFIED
1. DIMENSIONS ARE IN MILLIMETERS (INCHES).

2. WIRE: 32AWG. TWIST WIRES 1-2 TURNS/INCH.

3. DIRECTION OF LOOP ON POST IS OPTIONAL.
CRIMP TERMINALS MAY BE USED INSTEAD.

4. TERMINAL 50058-8100 MAY BE USED
AS A SUBSTITUTE.

5. MUST BE ROHS COMPLIANT,SEE EUROPEAN DIRECTIVE
2002/95/EC.

6. WORKMANSHIP TO BE COMPLIANT WITH THE
REQUIREMENTS OF IPC-A-610, CLASS 2.

TOLERANCES X ± 1.3 (.05) XX ± .50 (.02) XXX ± .13 (.005) ANGLES ± 1°		MAGTEK 20725 S. ANNALEE AVENUE CARSON, CA 90746	
DRAWN BY HUOY LOR		READ HD/SPRNG (S) TK1,2 65MM WRE, 5PMLX CONN	
DATE 21 OCT 2004	DESIGNER	SIZE B	DWG NO. 21052224
		SCALE 2X	D.01 REV 1
		SHEET 1	OF 1